

**150W Single output****Approvals: CE,UL****Size(L×W×H):199mm×98mm×38mm****Product features:**

- Universal AC input/ full range
- Power on indication
- Protections: Overload /Over voltage /Short circuit
- Compact, high reliability, high efficiency
- 100% full load burn-in test
- 2 - years warranty

Specifications:

AC Input voltage	88-132VAC/176-264 VAC selected by switch
Input frequency	47~63Hz
Inrush current	35A @230VAC, full load cold start
Hold up time	20ms@230 VAC full load
Overload protection	110%- 150%
Over voltage protection	110%-145%
Operating temperature	-20 ~ 70℃ refer to output derating curve
Safety standard	UL60950-1
EMC standard	EN55022 class B
MTBF	20 ⁵ Hrs at 25℃
Withstand voltage	I/P-O/P:3KV,1min I/P-FG:1.5KV,1min O/P-FG:0.5KV ,1min
Weight	0.7Kg/pcs

P/N	Output	Tol.	R&N	Effi.	Load Regulation	DC adjustment range
EPR-150-3.3	3.3V,30A	±4%	80mV	74%	±3%	3~3.6V
EPR-150-5	5V,26A	±3%	80mV	77%	±2%	4.75~5.25V
EPR-150-12	12V,12.5A	±3%	120mV	83%	±2%	10.8~13.2V
EPR-150-24	24V,6.5A	±3%	120mV	86%	±2%	21.6 V~26.4V
EPR-150-48	48V,3.3A	±3%	200mV	87%	±2%	43.2~52.8V